

## NON SLIP ADDITIVE

A crushed glass particle that is broadcast to achieve optimal texture qualities with a resin based floor coating system.

- \* Easy to use
- \* Excellent slip resistance
- \* Particle size 0.45mm - 0.62mm
- \* Extreme abrasion resistance



### Performance & Comparison\*

Product	NSA
Ease of application	Medium
Preparation	Medium
Durability	High
Maintenance	Medium

### Characteristics

Colour:	Clear
Solids (vol. %):	%
Gloss:	Low
Pack Sizes:	1kg & 4kg
Abrasion Resistance:	Excellent
Chemical Resistance:	Excellent
Solvent Resistance:	Excellent

### \*Performance Guide & Comparison

Description	Evaluation & Meaning
Ease of Application	The level of effort and expenditure to apply the coating, combined with level of expertise. <i>High = very easy to apply; Medium = easy to apply; Low = presents challenges for inexperienced users.</i>
Preparation	The level of effort and expense for preparing the substrate for coating. <i>High = a high level of effort and expertise required for preparation; Medium = modest preparation required; Low = low to no preparation required.</i>
Durability	The expected performance under standard Australian conditions for weathering and temperature variation. <i>High = High level of durability under extreme conditions; Medium = meets or exceeds standard conditions; Low = meets standard conditions, but not expected to endure.</i>
Maintenance	The level of continued coating support, or re-coating to achieve the same level of performance. <i>High = a high level of effort and expenditure in cleaning, or re-coating the system; Medium = a modest level of effort and expenditure for cleaning to keep the coating looking good and performing well; Low = almost no effort to support the coating system after application.</i>

**APPLICATION** Can be broadcast by hand into wet sealer.

Spread Rate	Minimum	Maximum	Typical
Theoretical Spread Rate (m <sup>2</sup> /kg)	5	10	7.5
Wet Film Thickness (Qm)	N/A	N/A	N/A
Dry Film Thickness (Qm)	N/A	N/A	N/A

**DRY TIMES \*\***

Substrate Temperature	5 °C	10 °C	20 °C	30 °C
Surface Dry (minutes)	N/A	N/A	N/A	N/A
Hard Dry (hours)	N/A	N/A	N/A	N/A
Recoat Time (hours)	N/A	N/A	N/A	N/A

*\*\* Drying times are generally related to air circulation, temperature, and film thickness. The figures given above are typical with good ventilation, typical film thickness and single coat application.*

**SURFACE PREPARATION**

It is recommended that surfaces are clean (free from any dirt, grease or other foreign matter) and dry.

**DIRECTIONS FOR USE**

Broadcast granules by hand into wet sealer. After drying, apply a second coat of sealer.

**SAFETY**

Provide adequate ventilation and wear protective clothing. Consult the Safety Data Sheet.

Failure to observe these precautions will void all warranties and guarantees for product performance. The manufacturer will take no responsibility for coatings, products, labour, corrective action, or compensation where there is evidence of a failure to abide by the manufacturer's directions.

**CLEAN UP**

N/A

**DISCLAIMER**

Do not apply this product if there is uncertainty about application or surface preparation. This Product Data Sheet is to be used as a guide only; it is NOT a specification.

**For more information**

**Email:** [support@rightchoicecoatings.com.au](mailto:support@rightchoicecoatings.com.au)

**Web:** [rightchoicecoatings.com.au](http://rightchoicecoatings.com.au)