

## CRACK REPAIR

A general use crack repair to be used on most concrete and masonry surfaces. Suitable for use on internal or external surfaces.



## APPLICATION

Apply using general patching trowel equipment.

## SURFACE PREPARATION

Ensure surface is clean and sound prior to applying.



## DIRECTIONS FOR USE

Mix fresh clean water to a consistent paste to suit application. In general, 1Kg of Crack repair to 200ml of water. Use the mixed product up within 30 minutes at 23°C.

Will dry after 14 days to 35 MPa. Wash over with a damp sponge if a smoother finish is required.

## THINNING

N/A

## PACK SIZES

1Kg

## DRYING TIMES

Dust Free:  
Touch Dry: 1 Hour  
Hard Dry: Overnight

## CLEAN UP

Wash up with water.

## COVERAGE

1kg at 10 mm deep x 10 mm wide will cover approx 5 lineal metres

## SHELF LIFE

Under normal conditions containers can be stored for up to 12 months before use.

## SAFETY

Advisable using gloves when handling.

## CLASSIFICATION

N/A

## DISCLAIMER

Due to differences in substrates, application methods and local conditions purchasers of this product must ensure that it is suitable for their specific application. Information contained in this Data Sheet is subject to standard terms & conditions of sale.

### For more information

**Email:** [support@rightchoicecoatings.com.au](mailto:support@rightchoicecoatings.com.au)

**Web:** [rightchoicecoatings.com.au](http://rightchoicecoatings.com.au)