



APPLICATION GUIDE

General Notes

- Ensure to read the TECHNICAL DATA SHEET, the PREPARATION GUIDE and the APPLICATION INSTRUCTIONS thoroughly first.
- Always wear the appropriate personal protection equipment
- It is recommended to do a test patch first to determine the suitability of the product
- Do not apply when the ambient temperature is below 15c or above 28c
- It is always advisable to apply sealers in the afternoon and in the shade
- Do not apply in direct sunlight when the temperatures exceed 28c
- The substrate must be cool to touch before applying any sealer or coating
- Do not apply if rain is imminent in the following 24 hours of application

Application

- Always follow the manufacturer's guidelines for coverage.
- Penetrating Sealer should be applied using a 10mm nap roller, applicator or back pack sprayer (with solvent resistant seals).
- Apply a saturation coat and allow to soak. If the product soaks in before 10 mins, apply a second application while still wet. It is ideal to see the surface wet with product for approximately 10 mins.
- After 10 mins, remove any excess sealer and move to the next area. Repeat the process.
- **DO NOT ALLOW EXCESS PRODUCT TO DRY ON THE SURFACE AS IT WILL GO WHITE.**
- Keep dry for a minimum of 12 hours.
- Do not walk on for a minimum of 6 hours.
- A subsequent coat can be applied 12 hours later for even further protection. Test a small area 1st to ensure that it penetrates within 10 mins. Begin with a very light application rate to that of the 1st. Only apply enough product to achieve penetration within 10 mins. **DO NOT OVERAPPLY OR IT WILL GO WHITE.**